


NOTES:

1. PIN ASSIGNMENT SEE TO WIRE LIST.
2. ELECTRICAL TEST CONDITION:
  - (a). 100% OPEN, SHORT & MISWIRE TEST,
  - (b). INSULATOR RESISTANCE: 10 Mohm MIN.  
DC 300V 0.01sec.
  - (c). CONTACT RESISTANCE: 3ohm MAX.

PIN ASSIGNMENT



4	OVERMOLD BLACK PVC 45P MA-001.	
3	USB3.1 C TYPE MALE BLACK INSULATOR SOLDER TYPE.	
2	USB3.1 C TYPE(3.1C-G4-C1) MALE BLACK INSULATOR SOLDER TYPE.	
1	(32AWG*1C+EAM)*4+32AWG*1P+32AWG*4C+2EAB(85%) OD:4.8MM L:152mm BLACK PVC JACKET UL2725.	
NO.	Description	P/N

DWG NO:	PCM-00167	GOODS CODE		Draw		Date	2019/3/28
ITEM NO.	P4198A	DRAWING EVIDENCE		Check		Date	
Goods NO.	C13166-002 - A			Approval	L.Fried	Date	
Original NO.	Unit(mm)						

PREMIER CABLE MFG CO LTD			D		
			C		
			B	CHANGE PIN OUT	2019/7/18
			VER.A	REVISE	Date.