



Notes:
Detailed Product Description:
1. Waterproof connector rating is IP67/IP68
2. Protected from dust and water during immersion, resistant to many oils and chemical etc.

Other Specification:
3. Rating voltage: 60V AC/DC
4. Rating current: 3A
5. Insulation resistance: >100MΩ.
6. Contact resistance of connector: ≤10mΩ.
7. Operating Temperature: -25°C ~ +85°C.

WIRE LIST

P1	COLOR	P2
1	BROWN	S/T
2	WHITE	
3	BLUE	
4	BLACK	

①	WSW P/N	L(mm)
	A-M08A04MST01016BK00	100±10
	A-M08A04MST02016BK00	200±10
	A-M08A04MST03016BK00	300±10

ITEM	SPECIFICATION	Q'TY	UNIT
⑥	M8*0.5 BRASS PLATED NI NUT L*W=2.0*1.0mm	1	PCS
⑤	BLACK EPOXY RESIN	1	G
④	O-RING BLACK FKM Ø7.00*1.5mm	1	PCS
③	M8 NICKEL PLATED BRASS NUT REAR PANEL MOUNT MALE SHELL	1	PCS
②	M8 A CODING 4 PIN MALE CONNECTOR	1	SET
①	UL1007 24AWG HOOK UP WIRE	1	SET

RoHS compliant
Unit: mm

Scale	Free					Date	Name	Customer-No.
TOLERANCE						Drawn	21.11.2018	Segal
.X	±0.5					Approved	26.01.2019	Amy
.XX	±0.20							
DIM	TOL	①	Update the P/N	26.01.2019	Segal			
X.	±2.0°	②	Drawn	21.11.2018	Segal			
.X	±1.0°							
Angle	TOL	Id.	Modification	Date	Name			

ASSMANN WSW-No. ① A-M08A04MSTxx016BK00	
Drawing-No. ASS 8412 CA	rev01
Replace	Sheet