



Product: <u>83003</u> ☑

Lead Wire, #24 Str SPC, TFE Ins, AWM 1213

Request Sample

Product Description

High Temp Plastic Lead Wire, 24AWG (19x36) Silver Plated Copper, TFE Insulation, AWM 1213 105C TYPE E MIL-W-16878/4 600V 200C

Technical Specifications

Product Overview

Suitable Applications: high temperature, inter-connection circuits, internal wiring of computer and electronic equipments, (Type E) MIL-W-16878/4 applications

Construction Details

Conductor

| Element | Number of Element | Size | Stranding | Material |
|--------------|-------------------|--------|-----------|----------------------|
| Conductor(s) | 1 | 24 AWG | 19x36 | SC - Silvered Copper |

Insulation

| | Material | Nom. Thickness | Nom. Insulation Diameter |
|---|--------------------------------|----------------------|--------------------------|
| | PTFE - Polytetrafluoroethylene | 0.01 in (0.25 mm) | 0.044 in (1.1 mm) |
| Ì | Overall Cable Diameter (Nomina | al): 0.044 in (1.1 m | m) |

Electrical Characteristics

Electricals

| Nom. Conductor DCR | Max. Current | | |
|--------------------|--|--|--|
| 24 Ohm/1000ft | Mil-Std-975M Table 3.16 (single wire): 3.3 A | | |

Voltage

UL Voltage Rating 600 V RMS

Mechanical Characteristics

Temperature

| UL Temperature | Operating |
|-----------------------|-----------------|
| 200°C | -70°C To +200°C |

Bend Radius

| Stationary Min. | Installation Min. | |
|-----------------|-------------------|--|
| 0.44 in (11 mm) | 0.44 in (11 mm) | |
| | | |

| Max. Pull Tension: | 5 lbs (2.3 kg) |
|--------------------|----------------|
| Bulk Cable Weight: | 2 lbs/1000ft |

Standards and Compliance

| Environmental Suitability: | Indoor, Outdoor |
|----------------------------------|-----------------|
| Sustainability: | CA Prop 65 |
| Flammability / Reaction to Fire: | VW-1 |
| AWM Compliance: | AWM 1213 |

| Military Compliance: | MIL-W-16878/4 |
|--------------------------------|---|
| European Directive Compliance: | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |

History

Update and Revision: Revision Number: 0.450 Revision Date: 06-30-2022

Part Numbers

Variants

| Item # | Color | Putup Type | Length | UPC | | | | |
|---------------|-------------|------------|----------|--------------|--|--|--|--|
| 83003 010100 | Black | Reel | 100 ft | 612825354857 | | | | |
| 83003 010500 | Black | Reel | 500 ft | | | | | |
| 83003 0101000 | Black | Reel | 1,000 ft | 612825353881 | | | | |
| 83003 006100 | Blue, Light | Reel | 100 ft | | | | | |
| 83003 006500 | Blue, Light | Reel | 500 ft | | | | | |
| 83003 0061000 | Blue, Light | Reel | 1,000 ft | | | | | |
| 83003 001100 | Brown | Reel | 100 ft | | | | | |
| 83003 0011000 | Brown | Reel | 1,000 ft | 612825399247 | | | | |
| 83003 008100 | Gray | Reel | 100 ft | | | | | |
| 83003 0081000 | Gray | Reel | 1,000 ft | 612825399285 | | | | |
| 83003 005100 | Green, Dark | Reel | 100 ft | | | | | |
| 83003 005500 | Green, Dark | Reel | 500 ft | | | | | |
| 83003 0051000 | Green, Dark | Reel | 1,000 ft | 612825399278 | | | | |
| 83003 003100 | Orange | Reel | 100 ft | | | | | |
| 83003 003500 | Orange | Reel | 500 ft | | | | | |
| 83003 0031000 | Orange | Reel | 1,000 ft | 612825399254 | | | | |
| 83003 002500 | Red | | | | | | | |
| 83003 002100 | Red | Reel | 100 ft | | | | | |
| 83003 0021000 | Red | Reel | 1,000 ft | 612825378327 | | | | |
| 83003 007100 | Violet | Reel | 100 ft | | | | | |
| 83003 0071000 | Violet | Reel | 1,000 ft | | | | | |
| 83003 009500 | White | | | | | | | |
| 83003 009100 | White | Reel | 100 ft | 612825354840 | | | | |
| 83003 0091000 | White | Reel | 1,000 ft | 612825378334 | | | | |
| 83003 004500 | Yellow | | | | | | | |
| 83003 004100 | Yellow | Reel | 100 ft | | | | | |
| 83003 0041000 | Yellow | Reel | 1,000 ft | 612825399261 | | | | |

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.