



# CRYSTEK MICROWAVE

A DIVISION OF CRYSTEK CORPORATION

## 18 GHZ PRECISION RF COAX CABLE ASSEMBLIES WITH STAINLESS STEEL CONNECTORS



### SS402 50 Ohm 18 GHz Precision Coaxial Cables

#### Features:

- Strain Relief:** Heavy duty adhesive strain relief
- Center Conductor:** SPCCS (Silver-Plated Copper Clad Steel)
- Inner Shielding:** SS (Spiral Strip Of Silver-Plated Copper)
- Outer Braid:** SPC (Silver-Plated Copper Braid)
- Insulation:** PTFE (Polytetrafluoroethylene) dielectric
- Jacket:** ETFE (Ethylene Tetrafluoroethylene Copolymer)
- Cable Outer Diameter:** 0.163" (4.14mm)
- Connectors:** SST, corrosion-resistant, per ASTM-A582 (Passivated finish per SAE-AMS-2700)
- Center Pin:** GPBC (Gold-Plated Beryllium Copper)
- Jacket Color:** Blue
- Operating Temperature:** -45°C to +85°C

**Minimum Bend Radius:** 0.8" (20.32mm)

*Custom Lengths Available*

#### Available Connector Terminations:

- SMA Male
- SMA Male Right Angle
- Type N Male
- Type N Bulkhead Female

#### Electrical Specifications:

- Impedance:** 50 Ohms
- Frequency:** 18 GHz
- Insertion Loss:** 0.66 dB/ft Typ at 18 GHz
- VSWR: (SMA)** <1.3 to 18 GHz
- (N-Type)** <1.35 to 18 GHz
- Nominal Capacitance:** 29 pF/ft
- Velocity of Propagation:** 70%
- Shield Effectiveness:** Greater than 110 dB
- Attenuation (dB/ft):** 0.08 Typical at 500 MHz
- \*connector loss not included* 0.11 Typical at 1 GHz
- 0.21 Typical at 3 GHz
- 0.32 Typical at 6 GHz
- 0.50 Typical at 12 GHz
- 0.66 Typical at 18 GHz



- Avg Power in (Watts):** 920 @ 500 MHz
- \*as specified at 25°C* 620 @ 1 GHz
- 360 @ 3 GHz
- 220 @ 6 GHz
- 150 @ 12 GHz
- 120 @ 18 GHz

#### Mechanical Specifications:

- Connector Corrosion (salt spray):** MIL-STD-202, method 101, test cond. B 5% salt solution.
- Connector Durability:** 500 connections Minimum

### SMA Male / SMA Male[Straight/Straight]

Part Number	Description	Length
CCSMA-MM-SS402-6	SS402 Precision Coax Cable, SMA Male Straight / Male Straight	6"
CCSMA-MM-SS402-12	SS402 Precision Coax Cable, SMA Male Straight / Male Straight	12"
CCSMA-MM-SS402-24	SS402 Precision Coax Cable, SMA Male Straight / Male Straight	24"
CCSMA-MM-SS402-36	SS402 Precision Coax Cable, SMA Male Straight / Male Straight	36"
CCSMA-MM-SS402-48	SS402 Precision Coax Cable, SMA Male Straight / Male Straight	48"
CCSMA-MM-SS402-60	SS402 Precision Coax Cable, SMA Male Straight / Male Straight	60"
CCSMA-MM-SS402-72	SS402 Precision Coax Cable, SMA Male Straight / Male Straight	72"
CCSMA-MM-SS402-120	SS402 Precision Coax Cable, SMA Male Straight / Male Straight	120"



**CRYSTEK  
CORPORATION**

12730 COMMONWEALTH DRIVE • FORT MYERS, FL 33913  
 PHONE: 239-561-3311 • 800-237-3061 Rev.: N  
 FAX: 239-561-1025 • WWW.CRYSTEK.COM Date: 08-02-22



**CRYSTEK**  
**MICROWAVE**  
 A DIVISION OF CRYSTEK CORPORATION

**18 GHZ PRECISION RF  
 COAX CABLE ASSEMBLIES  
 WITH STAINLESS STEEL  
 CONNECTORS**



**SMA Male [Straight/Right Angle]**

Part Number	Description	Length
CCSMA1-MM-SS402-6	SS402 Precision Coax Cable, SMA Male Straight / SMA Male R/A	6"
CCSMA1-MM-SS402-12	SS402 Precision Coax Cable, SMA Male Straight / SMA Male R/A	12"
CCSMA1-MM-SS402-24	SS402 Precision Coax Cable, SMA Male Straight / SMA Male R/A	24"
CCSMA1-MM-SS402-36	SS402 Precision Coax Cable, SMA Male Straight / SMA Male R/A	36"
CCSMA1-MM-SS402-48	SS402 Precision Coax Cable, SMA Male Straight / SMA Male R/A	48"
CCSMA1-MM-SS402-60	SS402 Precision Coax Cable, SMA Male Straight / SMA Male R/A	60"
CCSMA1-MM-SS402-72	SS402 Precision Coax Cable, SMA Male Straight / SMA Male R/A	72"
CCSMA1-MM-SS402-120	SS402 Precision Coax Cable, SMA Male Straight / SMA Male R/A	120"

**SMA Male[Right Angle/Right Angle]**

Part Number	Description	Length
CCSMA2-MM-SS402-6	SS402 Precision Coax Cable, SMA Male R/A / SMA Male R/A	6"
CCSMA2-MM-SS402-12	SS402 Precision Coax Cable, SMA Male R/A / SMA Male R/A	12"
CCSMA2-MM-SS402-24	SS402 Precision Coax Cable, SMA Male R/A / SMA Male R/A	24"
CCSMA2-MM-SS402-36	SS402 Precision Coax Cable, SMA Male R/A / SMA Male R/A	36"
CCSMA2-MM-SS402-48	SS402 Precision Coax Cable, SMA Male R/A / SMA Male R/A	48"
CCSMA2-MM-SS402-60	SS402 Precision Coax Cable, SMA Male R/A / SMA Male R/A	60"
CCSMA2-MM-SS402-72	SS402 Precision Coax Cable, SMA Male R/A / SMA Male R/A	72"
CCSMA2-MM-SS402-120	SS402 Precision Coax Cable, SMA Male R/A / SMA Male R/A	120"



**CRYSTEK**  
 CORPORATION

12730 COMMONWEALTH DRIVE • FORT MYERS, FL 33913  
 PHONE: 239-561-3311 • 800-237-3061  
 FAX: 239-561-1025 • WWW.CRYSTEK.COM

Rev.: N  
 Date: 08-02-22



# CRYSTEK MICROWAVE


A DIVISION OF CRYSTEK CORPORATION

## 18 GHZ PRECISION RF COAX CABLE ASSEMBLIES WITH STAINLESS STEEL CONNECTORS




Data plots contained within this specification are generated from actual production cable assemblies. This data represents the typical performance that can be expected from each cable assembly. The data is plotted from raw data without modification (ie: Smoothing or Averaging.)


PN: CCSMA-MM-SS402-120  
VSWR (S11)




PN: CCSMA-MM-SS402-120  
INSERTION LOSS (S12)



PN: CCSMA-MM-SS402-120  
INSERTION LOSS (S21)



PN: CCSMA-MM-SS402-120  
VSWR (S22)



**CRYSTEK**  
CORPORATION

12730 COMMONWEALTH DRIVE • FORT MYERS, FL 33913  
PHONE: 239-561-3311 • 800-237-3061 Rev.: N  
FAX: 239-561-1025 • WWW.CRYSTEK.COM Date: 08-02-22