

# HDMI to Micro HDMI Cable with Ethernet, Digital Video with Audio Adapter (M/M), 3 ft. (0.91 m)

MODEL NUMBER: P570-003-MICRO



#### Description

Tripp Lite's 3-ft. (0.91 m), HDMI to Micro HDMI High Speed w/Ethernet Audio/Video cable allow devices with Micro-HDMI output ports, such as Smart Phones, Cameras, Notebooks, and other portable devices, to attach to standard HDMI displays such as TV's, monitors, Projectors, etc. Cable complies with HDMI v1.4 specifications, and is capable of transferring 1080p, Ethernet, 3D video, as well as digital audio. Featuring a full 19-pin array like larger HDMI connectors, only in a miniaturized version, the HDMI Micro Connector saves space on portable devices, while allowing the full capabilities of current HDMI v1.4 digital signaling.

## **Features**

- 3-ft. (0.91 m) HDMI to Micro HDMI High Speed w/Ethernet Cable
- Compliant with HDMI v1.4 specifications, Type D Connector
- 1080p, 3D, Blu-Ray, Ethernet, Digital Audio transfer
- Mylar Foil and Braid Shielding for maximum noise suppression
- Rugged, molded connectors for a lifetime of use
- Gold plated contacts and connector shell assures highest signal quality

# **Specifications**

OVERVIEW		
UPC Code	037332165473	
Product Type	Passive	
Technology	НОМІ	
VIDEO		
Max Supported Video Resolution	1920 x 1080 @ 60Hz	

## **Highlights**

- 3-ft. (0.91 m) HDMI to Micro HDMI High Speed w/Ethernet Cable
- Micro HDMI connector is 50% smaller than standard HDMI
- Complies with HDMI v1.4 Type D connections
- Full 1080p, 3D, Blu-Ray, Ethernet, Digital Audio transfer

### **System Requirements**

 Device with Micro-HDMI output, to Display with standard HDMI Input

## Package Includes

 3-ft. (0.91 m) HDMI to Micro HDMI High Speed w/Ethernet Audio/Video Cable





Max Supported Color Depth	48-bit Deep Color	
HDR Support	No No	
3D Video Supported	Yes	
Chroma Sub Sampling	4:4:4	
EDID Support	Yes	
Signal Transmission	Bidirectional	
Olgital Hallottiloolott	Diametrical de la control de l	
AUDIO		
Audio Specification	ARC	
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators	0	
PHYSICAL		
Color	Black	
Material of Construction	PVC	
Cable Jacket Color	Black	
Connector Color	Black	
Cable Jacket Material	PVC	
Cable Jacket Rating	VW-1	
Cable Outer Diameter (OD)	4.5mm	
Wire Gauge (AWG)	34	
Cable Length (ft.)	3	
Cable Length (m)	0.91	
Ferrite Core	No	
Minimum Bend Radius	22.5mm	
Shipping Dimensions (hwd / in.)	0.25 x 4.70 x 9.10	
Shipping Dimensions (hwd / cm)	0.64 x 11.94 x 23.11	
Shipping Weight (lbs.)	0.20	
Shipping Weight (kg)	0.09	
ENVIRONMENTAL		
Operating Temperature Range	14 to 122 F (-10 to 50 C)	
Storage Temperature Range	5 to 140 F (-15 to 60 C)	
Operating Humidity Range	0% to 90% RH, Non-Condensing	
Storage Humidity Range	0% to 90% RH, Non-Condensing	





COMMUNICATIONS		
EDID Compatible	Yes	
Consumer Electronics Control (CEC) Supported	Yes	
CONNECTIONS		
Side A - Connector 1	MICRO HDMI (MALE)	
Side B - Connector 1	HDMI (MALE)	
Connector Plating	Gold	
Contact Plating	Gold	
Connector Style	Straight	
Latching or Gripping Connector	No	
FEATURES & SPECIFICATIONS		
HDCP Specification	1.4; 2.2	
EMI/RFI Line Noise Protection	No	
MST Support	No	
IP68 Rated	No	
Antibacterial	No	
Armored Cable	No	
Ethernet Support	Yes	
IP20 Rated	No	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; REACH	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>