

USB-A to RS232 (DB9) Serial Adapter Cable - (M/M), 5 ft. (1.52 m)

MODEL NUMBER: **U209-000-R**



Connect devices with a 9-pin RS-232 serial port, such as modems, digital cameras, PDAs and ISDN terminals, to the USB Type-A port on your computer or laptop.

Description

The U209-000-R USB-to-Serial Adapter Cable allows you to connect a 9-pin RS-232 serial device to a computer or laptop with a USB Type-A port. It works with modems, digital cameras, PDAs, ISDN terminals and other devices with a serial port. The U209-000-R supports data transfer speeds up to 230 Kbps—twice as fast as a built-in serial port. No external power is required, and the compact 5-ft. (1.52 m) cable tucks away conveniently in your backpack or laptop bag for easy travelling. Doubled-shielded design with gold-plated contacts, tinned copper braid and aluminum Mylar foil shield eliminates crosstalk and reduces EMI/RFI interference. Compatible with Windows 2000, XP, Server 2003, Vista, 7, Server 2008, 8, 8.1, Server 2012, 10 and 11; Mac OS X 10.6 through 12.4; and Linux Redhat 7.3, 8.0 and 9.0.

Features

- Connect a RS-232 Serial device to the USB port on your computer
- Connectors: USB-A male/DB9 male
- Portable design is ideal for use with a PDA or digital camera
- Does not require external power
- Supports data transfer rates up to 230 kbps
- Premium double-shielded cable with tinned copper braid and aluminum Mylar foil shield that eliminates cross-talk and reduces EMI/RFI interference
- Compatible with Windows, Mac and Linux computers
- Prolific PL2303RA Chipset

Specifications

OVERVIEW	
UPC Code	037332095640
Technology	Serial; USB

Highlights

- 5-ft. (1.52 m) Length
- No external power required
- Compatible with Windows, Mac and Linux computers, and Android Tablets / Phones (See System Requirements for details)
- Need drivers? Click on the Support Page link on the left

System Requirements

- Compatible with Windows 2000 up to 11
- Compatible with Mac OS X 10.6 through 12.4
- Compatible with Linux Redhat 7.3, 8.0 and 9.0 (Linux Kernel 2.4.31 and above already includes built-in drivers)

Package Includes

- U209-000-R USB-A to Serial Adapter (DB9) - (M/M), 5-ft. (1.52 m)
- Owner's Manual



Host Connector	USB A (MALE)
INPUT	
Bus Powered	No
PHYSICAL	
Color	Black
Material of Construction	PVC
Cable Jacket Color	Black
Cable Jacket Material	PVC
Cable Outer Diameter (OD)	5.0 +/- 0.15
Cable Length (ft.)	4.9
Cable Length (m)	1.49
Shipping Weight (lbs.)	0.24
Shipping Weight (kg)	0.11
Unit Dimensions (hwd / in.)	4.920 x 1.210 x 0.490
Unit Dimensions (hwd / cm)	150 x 3.08 x 1.25
Unit Packaging Type	Box
Unit Weight (lbs.)	0.1984
Unit Weight (kg)	0.09
ENVIRONMENTAL	
Operating Temperature Range	32 to 140F (0 to 60C)
Storage Temperature Range	-4 to 176F (-20 to 80C)
Relative Humidity	0 to 80% RH
CONNECTIONS	
Number of Ports	1
Side A - Connector 1	USB A (MALE)
Side B - Connector 1	DB9 (MALE)
Connector Plating	Gold
FEATURES & SPECIFICATIONS	
USB Specification	USB 2.0 (up to 480 Mbps)
Driver Required	No
Remote Wakeup Support	No



STANDARDS & COMPLIANCE	
Product Certifications	EN 55024; EN 55032
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>